



Specification

DISPLAY
Pixel pitch: 10mm
Module size: 320x320mm
Driving type: 1/2 scan
Module Resolution: 32(H)×32(V)
Density: 10000 pixels/m ²
Mask Pure Black mask-high contrast screen
Panel dimensions: 960x960x127mm
Cabinet Resolution: 96(H)×96(V)
Weight per panel: 29 kg
Operation Power: AC100-240V 50-60HZ Switch-able
Max Power: 563 W/Panel
Average Power: 188 W/Panel
Refresh rate: 1920-3840Hz
Brightness: 5500nits
View Angle: 140 degree (horizontal) 140degree(vertical)
View Distance: 10m-100m
Gray Scale: 14bits input, correction with 16bits
Correction Scale Level: 16bits
Frame Update Frequency: 60-75Hz
Gamma Correction: -5.0—5.0
Support Input: Composite Video, S-Video, DVI, HDMI., SDI, HD_SDI
Support VGA: Mode 800×600,1024×768,1280×1024,1600×1200
Color Temperature: 5000-9300 adjustable
Lifetime: 100000
Operating Humidity: 10-95% RH
Operating Temp.: -20-60 Celsius degree
MTBF: 5000 hours
Continuous Working Time: ≥48 hours
IP rating: IP65/IP54

P10 - OUTDOOR VIDEOTRON OUTDOOR




Outdoor Fixed LED Display

- High Quality LED Screen for Outdoor Application
- Customized Size as Customer's Requirement
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved



IP65 Protection Level



High Brightness, Excellent Image Video



Energy Saving



More Features



CONTRAST



MODULAR



LOW NOISE



24/7
OPERATION



COLOR



EASY
INSTALL



WIDE VIEW



SCALABLE