



P1.5 INDOOR LED DISPLAY INDOOR



SPECIFICATIONS

MODUL
Module size : 250 * 250 mm
Pixel resolution : 160*160 dots
Module Pixel : 25600dots
Pixel Pitch : 1.5 mm
CABINET
Material : die cast
Weight : Max 6 Kg/ Cabinet
Cabinet Size : 500 * 500 mm
SCREEN
Pixel Resolution : 320 dots*320 dots
Pixel Density : 409600 dots/m ²
Brightness : ≥600cd/m ² (diatas spesifikasi yang diminta)
Golden wire LED Lamp SMD 1515
Pixel Configuration : 1R1G1B
Refresh rate : 3840 Hz
Frame Frequency : ≥60Hz
Gray Scale Rectification : 16384 grades
Colors : 16384*16384*16384
Input citage & Input Power Frequency : AC200 240V (50-60Hz)
View Angle : H160° / V160°
Driving Mode : 1/40 scan static
Operating Temperature : - 20° G + 45° C
Average No-Failure Time : > 8.000 hs
Life Span : > 75.000 hours
Control Distance : CAT 5 Cable
Connection method : Synchronized with Computer : If TV, DVD player, VCD player, VCR, etc (need video processor)
Signal Input format : DVI
Certificate : TUV CE, FCC, ETL, CNAS
Maintenance way : Full Front
Average Power Consumption : 200W/m2
Max. Power Consumption : 600W/m2
Continuous Working Time : 72hours
Water Proof : IP31



High Brightness, Excellent Image Video



Energy Saving

Indoor LED Display

- High Quality LED Display for Indoor Application
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved
- Customize Size



More Features

