

Specification

DISPLAY	
Videotron	P8 Outdoor
Pixel Pitch	8mm
Pixel Configuration	1R1G1B (3 in 1)
Module Pixel	40x40 = 1600 dots
Drive IC	ICN 2037
Scan Mode	1/4
Module Thickness	17mm
LED Package (Type)	Nation Star SMD3535
Cabinet Size	960 mm x 960 mm x 140 mm
Cabinet Resolution	120x120dots
Pixel Density	15625dot/m2
Cabinet Weight (Kg)	42 ±0.05
View Angle	Horizontal 120° Vertikal 120°
Brightness / Adjustment	6500 cd/m2
Best Viewing Distance	8-30m
Failed Rate	< 0.0002
Refresh Rate	2880-3840 Hz
Operation Voltage	AC220V/100V±15%
Color quantity	16.7M
Power Consumption	450W/sqm
Life span	≥100,000 hours
Protective Grade	IP65
Work Temperature	0°C ~ 50°C
Humidity	10% ~ 90%
Controlling system	Synchronization
Input signal	RF, S-Video, RGB, RGBHV, YUV, YC, SDI, HD-SDI, DVI, UXGA, COMPOSITION, etc.
Display Function	Text, news, advertising, flash, animation
Certificate	CE, FCC, ROHS, 3C, ISO9001:2008
Working Voltage	40A 5V

P8 - OUTDOOR LED DISPLAY




Outdoor Fixed LED Display

- High Quality LED Screen for Outdoor Application
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved
- Customize Size



IP65 Protection Level



High Brightness, Excellent Image Video



Energy Saving



More Features

