

SPECIFICATIONS

CABINET	
Pixel pitch	2.5 mm
Type Lamp LED	SMD 2020
Module Size	160x160mm
Module Resolution	64dots X 64dots
Pixel configuration	1RGB
Cabinet material	Alumunium extrusion
Cabinet Size (WxHxD)	480mmx480mm
Cabinet Resolution	192x192dots
Density	160.000 dots/m ²
Weight of cabinet	9 KG
Support hanging or not	No
MAIN	
Best viewing distance	>2.5 m
PARAMETER	
Brightness	>1200cd/m ²
Driving method	1/40 scanning
Best viewing angle	≤110°
Out-of control point	<0.0001
Refresh frequency	>3840Hz
Working voltage	AC220V/110V±10%
Colors	>16.7M
Power consumption	Max ~900W/m ² ; Avg ~450 W/m ²
Life span	100,000Hours
Maintenance	Front & Rear
IP grade	IP30
Gray scale	14bits
Color temperature	6500K
Control method	Asynchronization/Synchronization
Frame frequency	60Hz
Working temperature	-20°C~50°C±10%
Display Function	Text, news, advertising, flash, animation
Working Voltage	40A 5V
Brightness Control	256 grade
MTBF	10,000Hours

P2.5 INDOOR LED DISPLAY INDOOR





High Brightness, Excellent Image Video



Energy Saving

Indoor LED Display

- High Quality LED Display for Indoor Application
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved
- Customize Size



More Features

