

SPECIFICATIONS

DISPLAY	
Pixel Pitch	2.5mm (P2.5)
Module Size	320x160mm
Brightness	≥ 1.000 Nits
LED Type	SMD 2121
Refresh Rate	>1920Hz
Pixel Density	160000 dots/m ²
Scanning Type	1/32 Scanning
View Angle Horizontal	140°
View Angle Vertical	120°
View Distance	2.5m-25m
Display Color	16.7M
Brightness Adjustment	0-100 levels
Operating Life	>100.000 hours at 50%
Operational Input Voltage	200 - 240 V / 50-60Hz
Operating Temperature	-20°C min. / +50°C max
Operating Humidity	10% min. / 90% max
Protection Level	IP54
Magnetic Maintenance	Front and Rear
Control Distance	100 meter via LAN cable
Gamma Correction	-5.0—5.0
Support VGA Mode	800×600,1024×768,1280×1024,1600×1200
Color Temperature	5000-9300 adjustable
Support file	AVI, MPEG, MP4, FLV, WMV, MOV, DVD, etc.
Operating System	Windows 7 / Windows 10

P2.5 INDOOR LED DISPLAY INDOOR





High Brightness, Excellent Image Video



Energy Saving

Indoor LED Display

- High Quality LED Display for Indoor Application
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved
- Customize Size



More Features

