



SPECIFICATIONS


DISPLAY	
Videoscreen OUTDOOR PERMANENT MODULAR P6	
Screen Size	5,952 x 3,840 mm
Display Resolution	992 x 640 Dot / Px (HD Resolution)
Total Resolution	634,880 dot/px
Pixel Pitch	6 mm
Density	27,777 dot/sqm
Contrast	64,000 : 1
Module Qty	620 Pcs Permanent Module Systems
Cabinet Structure	Fixed Permanent Module Systems
Gross Weight	500 Kgs
LED Chip Certification	Standard LED Chip (Can be Upgraded)
LED Processor	Built-in
LED Model	PH-6 Permanent Module Systems
LED Arrangement	1R 1G 1B SMD2727 Outdoor
LED Type	SMD 2727 - Standard LED
Module Size	192 x 192 mm
Module Resolution	32 dot x 32 dot
Mask	Pure Black mask-high contrast screen
Brightness	≥6500cd/m ²
View Angle	140 degree (horizontal) 140degree(vertical)
View Distance	6m-60m
Grayscale	16 bit
Display Color	16.7M
Brightness Adjustment	0-100 levels
Operation Power	AC100-240V 50-60HZ Switch-able
Power Consumption	Max : < 600 W/m ² Average: 250W/m ²
Refresh Rate	High Refresh Rate: >2000 Hz
Gamma Correction	-5.0 - 5.0
Support Input	Composite Video, S-Video, DVI, HDMI., SDI, HD_SDI
Support VGA Mode	800×600,1024×768,1280×1024,1600×1200
Color Temperature	5000-9300 adjustable
Operating Temp.	-20-60 Celsius degree
Operating Humidity	10-95% RH
Operating Life	100,000 hours
Protection Level	IP43 Waterproof
Warranty	Full Service + Spareparts: 1 Years

P6 - OUTDOOR VIDEOTRON OUTDOOR





IP43 Protection Level



High Brightness, Excellent Image Video



Energy Saving

Outdoor Fixed LED Display

- High Quality LED Screen for Outdoor Application
- Customized Size as Customer's Requirement
- SMD 3 in 1 LED Encapsulation Technology
- CE,Rohs Approved



More Features



CONTRAST



MODULAR



LOW NOISE



24/7
OPERATION



COLOR



EASY
INSTALL



WIDE VIEW



SCALABLE